




57219 12V72Ah



Dimensions (mm)




Physical Specification (mm)

Nominal Voltage		12V
Nominal Capacity(20HR)		72Ah
Dimension	Length	278+0/-2mm(10.94inches)
	Width	175 +0/-2mm(6.89inches)
	Container Height	190 +0/-3mm(7.48inches)
	Total Height(with Terminal)	190 +0/-3mm(7.48inches)
Weight		Approx 17.2Kg(37.93lbs)
Acid		1.280±0.015g/cm ³ (25°C)
Standard Terminal		1
Cell layout		1
Hold-Down		B13
Cell plate qty		/
Case		Black-PP Material
Cover		Black-PP Material
Handle		Black-PP Material
QTY/PLT/layer		/

Electrical Specification

Rated Capacity	20 hour rate(3.6A)	72Ah
Reserve Capacity	122min	
Cold Cranking Performance Amps@0°F(-18°C)	620A	


Discharge Characteristics(25°C,70°F)



Standard Terminal (mm)


Cell Layout

Terminal Type	D	
	Positive	Negative
1	19.5 ⁰ _{-0.3}	17.9 ⁰ _{-0.3}



Figure(1)

Discharge Characteristics(-18°C,0°F)



*Values are subject to variation of +/- 5% in normal manufacturing processes.
*Technical specifications and the product line above could be changed without prior notice.