




LEOCH BATTERY

JIS 75D23L (12V63Ah)



Dimensions (mm)




Physical Specification (mm)

| | | |
|------------------------|-----------------------------|-------------------------------------|
| Nominal Voltage | | 12V |
| Nominal Capacity(20HR) | | 63Ah |
| Dimension | Length | 231.5±2mm(9.11inches) |
| | Width | 172±2mm(6.77inches) |
| | Container Height | 202±2mm(7.95inches) |
| | Total Height(with Terminal) | 223±2mm(8.78inches) |
| Weight | | Approx 15.9Kg(35.06lbs) |
| Acid | | 1.280±0.015g/cm ³ (25°C) |
| Standard Terminal | | 1 |
| Cell layout | | 0 |
| Hold-Down | | B0 |
| Cell plate qty | | / |
| Case | | Black-PP Material |
| Cover | | Black-PP Material |
| Handle | | Black-PP Material |
| QTY/PLT/layer | | / |

Electrical Specification

| | | |
|---|---------------------|--------|
| Rated Capacity | 20 hour rate(3.15A) | 63Ah |
| Reserve Capacity | | 104min |
| Cold Cranking Performance Amps@0°F(-18°C) | | 550A |


Discharge Characteristics(25°C,70°F)



Standard Terminal (mm) Cell Layout

| Terminal Type | D | | Cell Layout Diagram |
|---------------|-----------------------------------|-----------------------------------|---------------------|
| | Positive | Negative | |
| 1 | 19.5 ⁰ _{-0.3} | 17.9 ⁰ _{-0.3} | <p>Figure(0)</p> |

Discharge Characteristics(-18°C,0°F)



*Values are subject to variation of +/- 5% in normal manufacturing processes.
 *Technical specifications and the product line above could be changed without prior notice.