




# LP Series-General Purpose LP12-7.0E(12V6.0Ah)




## Specifications

Rated Voltage	12V	
Nominal Capacity	6.0Ah	(C <sub>20</sub> , 1.75V/cell)
Dimension	Length	151±2mm (5.95 inches)
	Width	65±1mm (2.56 inches)
	Container Height	93.5±1mm (3.68 inches)
	Total Height	99.5±1mm (3.92 inches)
Approx Weight	1.81 Kg (3.99 lbs)	
Terminal	T1/T2	
Container Material	ABS	
Rated Capacity (25°C)	6.00 Ah	(20hr, 0.300A, 1.75V/cell)
	5.59 Ah	(10hr, 0.559A, 1.75V/cell)
	5.15 Ah	(5hr, 1.03A, 1.75V/cell)
	4.59 Ah	(3hr, 1.53A, 1.75V/cell)
	3.94 Ah	(1hr, 3.94A, 1.60V/cell)
Max. Discharge Current	90A (5s)	
Internal Resistance (25°C)	Approx 27mΩ	
Operating Temp. Range	Discharge	-15 ~ 50°C (5 ~ 122°F)
	Charge	-20 ~ 40°C (-4 ~ 104°F)
	Storage	-15 ~ 40°C (5 ~ 104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 1.8A. Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
	Initial Charging Current less than 1.8A. Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Effect of temp. to Capacity	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	LP series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



## Layout



## Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	16.7	12.3	9.93	8.10	6.02	4.42	3.61	2.64	2.07	1.49	1.18	1.01	0.860	0.676	0.546	0.294
1.80V/cell	18.1	12.9	10.3	8.35	6.18	4.51	3.68	2.68	2.10	1.51	1.20	1.02	0.871	0.684	0.552	0.297
1.75V/cell	19.6	13.6	10.7	8.60	6.32	4.60	3.75	2.73	2.13	1.53	1.21	1.03	0.882	0.692	0.559	0.300
1.70V/cell	21.1	14.2	11.1	8.86	6.47	4.69	3.81	2.77	2.17	1.55	1.23	1.05	0.894	0.701	0.566	0.303
1.67V/cell	21.9	14.6	11.3	9.01	6.56	4.74	3.85	2.80	2.19	1.57	1.24	1.05	0.900	0.706	0.570	0.305
1.60V/cell	23.9	15.5	11.8	9.36	6.76	4.87	3.94	2.86	2.23	1.60	1.26	1.07	0.916	0.718	0.579	0.309

## Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	31.8	23.5	19.1	15.6	11.6	8.58	7.03	5.15	4.05	2.92	2.33	1.98	1.70	1.34	1.08	0.588
1.80V/cell	34.3	24.6	19.7	16.0	11.9	8.72	7.14	5.22	4.10	2.96	2.36	2.01	1.72	1.35	1.10	0.594
1.75V/cell	36.8	25.7	20.3	16.4	12.1	8.86	7.24	5.29	4.15	3.00	2.39	2.03	1.74	1.37	1.11	0.600
1.70V/cell	39.3	26.7	20.9	16.8	12.3	8.99	7.34	5.37	4.21	3.03	2.41	2.06	1.76	1.39	1.12	0.606
1.67V/cell	40.7	27.3	21.3	17.1	12.5	9.07	7.40	5.41	4.24	3.06	2.43	2.07	1.77	1.40	1.13	0.610
1.60V/cell	43.9	28.8	22.1	17.6	12.8	9.26	7.54	5.50	4.31	3.11	2.47	2.10	1.80	1.42	1.15	0.619



# LP Series-General Purpose LP12-7.0E(12V6.0Ah)



## Applications

- All purpose
- Uninterruptable Power Supply (UPS)
- Electric Power System (EPS)
- Emergency backup power supply
- Alarm and security system
- Communication power supply
- DC power supply
- Auto control system


## General Features

- 5 years design life(25°C)
- Special exhaust structure and sealing technology, safe and reliable, flexible installation, convenient maintenance
- PbCaSn alloy for plate grids: less gassing, less self-discharging
- High quality AGM separator: extend cycle life and prevent micro short circuit
- High purity raw material: ensure low self discharge rate


## Standards

- Compliance with IEC 60896 standards, EU Battery Directive
- UL, CE Certified
- Manufactured in Leoch®IATF 16949, ISO45001, ISO 9001 and ISO 14001 certified production facilities


## Discharge Characteristics




## Float Charging Characteristics



## Temperature Effects in Relation to Battery Capacity



## Float Service Life



## Sales Offices Worldwide

### China Sales Office

5th Floor, Xinbaohui Bldg., Nanhai Blvd.,  
Nanshan, Shenzhen, China. 518052  
Tel: +86-755-86036060 (100 lines)  
Tel: +86-755-26067269  
Fax: +86-755-26067269  
E-mail: export@leoch.com

### HongKong Sales Office

Workshop C, 33/F, TML Tower, No. 3 Hoi Shing Road,  
Tsuen Wan, New Territories, Hong Kong  
Tel: +852 35786666  
Tel: +44(0) 1452 729428 / 1452 729696  
Fax: +44 1452 690125  
E-mail: sales.hk@leoch.com

### Singapore Sales Office

No. 1 Tech Park Crescent,  
Singapore 638131  
Tel: +65 68636078  
Tel: +65 6863 6079  
Fax: +65 6863 6079  
Email: sales.sg@Leoch.com

### Australia Sales Office

2 /29 Tarlington Place, Smithfield, NSW 2164  
Australia  
Tel: 02 9756 0950  
E-mail: sales.au@leoch.com

### North America Sales Office

19751 Descartes  
Foothill Ranch, CA 92610, USA  
Tel: 949-588-5853  
Tel: 949-588-5853  
Fax: 949-588-5966  
E-mail: sales@leoch.us  
Http:// www.leoch.us

### UK Sales Office

9B Wheatstone Court, Waterwells, Business Park,  
Gloucester, GL2-2AQ, UK United Kingdom  
Tel: +44(0) 1452 729428 / 1452 729696  
Tel: +44 1452 690125  
Fax: +44 1452 690125  
E-mail: Sales.Europe@leoch.com  
Http:// www.leoch.eu

### EMEA Sales Office

1 Deligiorgi St., 121 31 Athens,  
Greece  
Tel: +30 210 5760318 (2 lines)  
Tel: +30 210 5760318 (2 lines)  
E-mail: support\_EMEA@leoch.com  
Http:// www.leoch.eu

### India Sales Office

Shed no.A-53(b), 2nd Stage of Peenya Industrial Area,  
Bangalore North Taluk, Bangalore-560058, India  
Tel: +91-80-23440018/23440019  
Tel: +91-80-23440017  
Tel: +91-80-23440017  
E-mail: indiasales@leoch.com



[Http://www.leoch.com](http://www.leoch.com)

© 2020 LEOCH. All rights reserved.

Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.  
Subject to revisions without prior notice.

Publication No.: LB-LP12-7.0E-PD-EN-V2.0-202004